



REVISIONS				
ZONE	LTR	DESCRIPTION	DATE	APPROVED

- CHARACTERISTICS
- OPERATING TEMPERATURE
OPEN: 165° +/- 6F
CLOSE: 145° F +/- 6F
 - BASIC THERMOSTAT: 4344 STYLE
 - DIELECTRIC STRENGTH: 1250 VAC FOR 1 MINUTE
TERMINALS TO CASE
 - MATERIAL: HOUSING CDA 360 BRASS
 - CONTACTS: GOLD FLASHING OVER SILVER

- NOTES:
- MARK DEVICE WITH "KLIXON ® MADE IN USA" AND TI PART NO. MARKING CAN BE DONE AROUND .705 MAX. DIA.
 - ORIENTATION OF WIRE LEADS TO DEVICE CENTERLINE IS NOT CONTROLLED.

NEITHER THIS PRINT NOR THE INFORMATION CONTAINED THEREON IS TO BE USED AGAINST THE INTEREST OF TEXAS INSTRUMENTS, INC. OR AGAINST THE INTERESTS OF ANY OF ITS AFFILIATED COMPANIES OR WHOLLY OWNED SUBSIDIARIES.

FOR REFERENCE ONLY
CONSULT TEXAS INSTRUMENTS
CUSTOMER SERVICE FOR LATEST
REVISION BEFORE USE

THIS IS A CAD DRAWING. THE GEOMETRY IN THE ASSOCIATED CAD COMPUTER FILE IS DIMENSIONALLY ACCURATE. WHEN DRAWING IS BEING REVISED, THE GEOMETRY MUST BE UPDATED IN ALL VIEWS AND ON ALL SHEETS.							
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES.	DRAWN	S. MARQUIS	DATE	5/12/02	TEXAS INSTRUMENTS ATILEBORO, MA 02705		KLIXON CONTROL PRODUCTS DIVISION
TOLERANCES ON FRACTIONS DECIMALS ANGLES	ENGINEER				TITLE		
	APPROVED				THERMOSTAT SWITCH ENVELOPE DRAWING		
MATERIAL	APPROVED				SIZE	CODE IDENT NO.	
					B	82647	28303-TBD
SIGNATURES ON FILE. REFER TO ELECTRONIC CHANGE NOTICE.				SCALE	SHEET		